

Wood Moisture Meter

Features:

- CE-Mark approval
- Portability and simplicity one-hand operation
- According EN50081-1(97)
- According EN50082-1(97)
- Automatic power shut off for maximum battery life.
- Jack socket for pin extension leads
- Three lights to indicate moisture content in wood:
 - Green: "Air, dry" conditions
 - Yellow: Slightly in excess of normal
 - Red: Excess moisture
- Measuring principle is electrical resistance
- Valox housing to withstand accidental drops
- Attached carrying case

Model: 690



Applications:


- Indoor
- Outdoor
- Furniture
- Environment studies

Specifications:

Display: 3 LEDs and 3½ digit liquid crystal display (LCD).

Range: 8% ~ 28%

(Reading above 28 indicate increasing levels of high moisture are not percent moisture content.)

Low battery indication: The "  " is displayed when the battery voltage drops below the operating level.

Operating environment: 0°C to 40°C, 15 to 80% R.H..

Storage environment: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

Accuracy: Stated accuracy at 23°C±5°C, <75% R.H.

Dimensions: 193mm(H) x 44mm(W) x 40mm(D).

Weight: Approx. 150g including battery (1.5VX4pcs AAA size).



CHY FIREMATE CO., LTD.
NO.3 SHENG-LI 1ST STREET, HSIN-TIEN VILLAGE,
JEN-TE HSIANG, TAINAN HSIEN, TAIWAN R.O.C.

Tel : 886-6-2794811
Fax : 886-6-2700227
E-Mail : chy@ksts.seed.net.tw