


HIGH CONCENTRATION SALINITY METER


MODEL: 391



FEATURES:

- Portability and simplicity one hand operation.
- Display Back-Light feature.
- Dual display Salinity & Temperature .
- Automatic Temperature Compensation.
- Average calculation, interval measuring, gram-conversion.
- Use highly accurate NTC temperature sensor.
- Hand-Held lightweight design.
- Auto power off function.
- CE-Mark Approval.

SPECIFICATIONS

- Low battery indication: the "  " is displayed when the battery voltage drops below the operating level.
- Operating environment: 0°C to 50°C at <70% R.H.
- Storage temperature: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.
- Accuracy: Stated accuracy at 23°C±5°C, <75% R.H.
- Dimensions: 178mm(H) x 65.5mm(W) x 35mm(D).
- Weight: 320g (including probe and battery)

TEMPERATURE

- Sensor: Thermistor temperature sensor
- Range: -20°C to 60°C
-4°F to 140°F
- Resolution: 0.1°C / 0.1°F
- Accuracy: ±0.5°C 0°C to 45°C
±1°C -20°C to 0°C, 45°C to 60°C
±1°F 32°F to 113°F
±2°F - 4°F to 32°F, 113°F to 140°F

RELATIVE SALINITY

- Range: 0.1% to 10%
- Temperature compensation: -5°C to 60°C, Automatic
- Accuracy:

- 0% to 0.9% (± 0.1)
- 1.0% to 1.9% (± 0.2)
- 2.0% to 2.9% (± 0.3)
- 3.0% to 4.9% (± 0.5)
- 5.0% to 5.9% (± 0.7)
- 6.0% to 7.9% (± 1.0)
- 8.0% to 10.0% (±1.5, depend on the way of measuring)

CHY FIREMATE CO., LTD.

NO.3, SHENGLI 1st ST., XINTIAN VILLAGE,
RENDE DISTRICT, TAINAN CITY, TAIWAN R.O.C.
TEL: 886-6-2794811 FAX: 886-6-2700227
E-mail: chy@chy-meter.com