



K-TYPE SINGLE CHANNEL THERMOMETER MODEL: 800



FEATURES:

- Highly accurate thermometer with 0.1% basic accuracy.
- Large display for easy to read.
- Thermocouple offset adjust.
- Robust protective Holster.
- Auto-Power Off.
- Display back-light.
- MIN/MAX/AVG/REL/HOLD functions.
- Wide measuring ranges suit for versatile applications.

GENERAL SPECIFICATIONS

- Display: 3½ digit liquid crystal display (LCD) with a maximum reading of 1999.
- Polarity: Automatic, positive implied, negative polarity indication.
- Low battery indication: The "E" is displayed when the battery voltage drops below the operating level.
- Measurement rate: 2.5 times/second.
- Operating environment: 0°C to 50°C at <70% R.H.
- Storage temperature: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.
- Accuracy: Stated accuracy at 23°C±5°C, <75% R.H.
- Battery: 1.5Vx4pcs AAA size.
- Dimensions: 160mm(H) x 83mm(W) x 38mm(D).
- Weight: approx. 235g including batteries.

TEMPERATURE RANGE:

Range: -200°C to 1372°C, -328°F to 1999°F

Accuracy:

±(0.1% rdg+1°C) on -60°C to 1372°C

±(0.1% rdg+2°C) on -60°C to -200°C

±(0.1% rdg+2°F) on -76°F to 1999°F

±(0.1% rdg+4°F) on -76°F to -328°F

K-type(Chromic -Alum)

CHY FIREMATE CO., LTD.

NO.3, SHENGLI 1st ST., XINTIAN VILLAGE,
RENDE DISTRICT, TAINAN CITY, TAIWAN R.O.C.

TEL: 886-6-2794811 FAX: 886-6-2700227

E-mail: chy@chy-meter.com